



Published on: 01/12/2010
Reviewed on: 01/10/2022

Ecwa NS908

TECHNICAL DATA SHEET

DESCRIPTION

Ecwa NS908 is a Nonionic Surfactant blend of Fatty Alcohol Polyglycol Ether.

FORMULATION/COMPOSITION

Ecwa NS908 is a Nonionic Surfactant blend of both Straight chain and Branched chain fatty alcohol hydrophobes.

2. Composition:

- a. % Straight Chain Fatty Alcohol Ethoxylates | Proprietary
- b. % Branched Chain Fatty Alcohol Ethoxylates | Proprietary

PROPERTIES/APPLICATIONS/USE

Ecwa NS908 is essentially designed as an Environmentally Safe 1:1 Drop-In Replacement for NP9 in the General Cleaning and Degreasing Formulations, in order to cover the requirements for:
Dispersancy; Emulsification; Wetting; General Detergency; Foam Stability and Rinseability.

Ecwa NS908 is Suitable/Compatible for use in the following Product Classes:

HI & I Cleaners/ Dishwashing Liquid and Degreasers / Hard Surface Cleaners / Agrochemicals Industrial Hand Cleaners & Hand-Soaps / Auto Care Products / Metal Cleaners /Dust Control/ Paper & Textile Processing / Paints & Coatings Etc.

Ecwa NS908 is Soluble in Water and most Polar Solvents.

Ecwa NS908 is Chemically stable in the presence of Dilute Acids, Bases and Salts.

Ecwa NS908 is Compatible with Soaps, Anionic & other Nonionic Surfactants & most Polar Organic Solvents.

PHYSICAL & CHEMICAL PROPERTIES

Physical state	Liquid	Flash Point (Closed Cup, ASTM 93)	247°C
Appearance	Colourless Clear/ Turbid	Colour (APHA)	MAX 5
Odour	Typical	HLB	13.25 ± 0.15
Relative Density	1.02 - 1.04 g/cm ³ @ 20°C	Degree of ETHOXYLATION	Proprietary Blend of Fatty Alcohol Ethoxylates in Water - 80% Concentrate
Solubility	Soluble in water		
pH (20°C- 1% Aq.Sol)	6.00 - 8.00		
Cloud Point (1% Aq.Sol)	64°C : ± 3°C		

This data does not constitute a specification - please see current "Certificate of Analysis".

MANUFACTURER/SUPPLIER

Ecwamix Chemical Systems (Pty) Ltd
3 Granville Avenue Lea Glen Rodepoort, Gauteng South Africa

Information
Tel: (o/h) +27 011 472 2256 Fax: +27 011 472 2121
E-mail: ecwamix@netactive.co.za

Emergency contact:
Office hours: 011 472 2256



SAFETY & HANDLING

Always consult the Material Safety Data Sheet before Use



Published on: 01/12/2010
Reviewed on: 01/10/2022

Ecwa NS908

TECHNICAL DATA SHEET

FORMULATION HINTS

Where Thick Gel-like products are desired, we recommend the use of such techniques as the interplay between SLES, CDE, SULPHONIC ACID and SALT to achieve this, rather than to try thickening the products by using the Gel-Phase of a chosen surfactant, which in most cases are simply a waste of surfactant.

The inclusion of nonionic surfactants with an HLB similar to **Ecwa NS908/NS906** in a formula assists with good wetting as well as good rinsing off of all surfaces after the formulated product has performed its Primary Function. For this reason, even if a formula is based largely on the use of Anionic Surfactants (SLES/ SDDBSA/ SLABS), it is always advisable to include even as little as 0.5% of **Ecwa NS908/NS906** in the cleaning formula, where the final dilution of the product is up to 20-50 times. Where products are largely based on high-alkalinity cleaning functionality, they often lose rinseability, something that every user of a Cleaner/ Degreaser-type product deplores, because a product can only clean to the level of how well one can rinse it off after cleaning.

Ecwa NS908/NS906 will not play a big role in the Rheology of a Formulation and will likewise only exhibit moderate abilities to Hydrotrope the inclusion of Salts. For high level of salts we recommend that a suitable hydrotrope be incorporated in order to stabilise your formula.

STORAGE

This product should be stored in its original packaging (tightly sealed), indoors in ambient conditions, between 10°C - 38°C. Under these storage conditions, this product will be stable for up to 2 years. Thereafter test parameters should be confirmed before use.

PACKAGING

Ecwa NS908 is available in	HLB Range
25 Kg - HDPE BLOWPACK	1. < 10: W/O Emulsifier
200 Kg - HDPE BLOWPACK	2. > 10: O/W Emulsifier
1000 Kg - IBC (FLOBIN)	3. 10 - 15: Good Wetting
	4. 12 - 15.....: Detergents

SPECIAL NOTES/CAUTIONS

Although **Ecwa NS908/NS906** is recommended as a Drop-In Replacement for NP9 used in formulations, due to the Proprietary nature of Specific/Special Formulations, this product should always be Tested for Usage Level/Suitability for use within a formula before Batching-Up.

Due to **Ecwa NS908/NS906** being a blend, stir or agitate mildly after prolonged storage periods or inactivity and after having been exposed to extreme temperature fluctuations.

DISCLAIMER / NON-WARRANTY

This product has been subjected to limited tests and has been shown to perform well. The information contained herein is to our best knowledge true and accurate, but since the conditions of use are beyond our control, Ecwamix Chemical Systems cc. disclaims any liability in connection with the use of this product and/or information. Warranty extends only as far as to the replacement of material shipped if not compliant with the specification as set out in the attached "Certificate of Analysis" and within the expiry period of the said product. All recommendations or suggestions are made without guarantee. It is good practice to conduct one's own application tests on a small area prior to using the product.



SAFETY & HANDLING

Always consult the Material Safety Data Sheet before Use